

tesa® Professional 60953 Anti-slip tape Glow in the dark

The application area for tesa® Anti Slip Professional range is everywhere safe footing is required. Anti Slip fluorescent is the ideal protection to prevent from skidding and therefore helps to avoid accidents in the job related. Very good adhesion of the product is suitable for demanding surfaces such as factory floors, industry areas etc. The strong and durable adhesive coating secures a high Anti Slip effect of up to 1- 2 years in normal use areas. The Anti Slip tapes are hand tearable and no shrinkage occurs after application. The phosphorescent tape 60953 creates safe footing in shaded, or even totally dark surroundings / rooms.

Main Application

- Indoor and outdoor applications * Applications in which a secure grip underfoot is required * Fluorescent (tesa® 60953): stays bright for a long period for safety and warning purposes in dark rooms * Transparent (tesa® 60952): make valuable surfaces such as wooden stairs, for example, safe unobtrusively * Black-yellow (tesa® 60951): marking of very slippery surfaces

Technical Data

▪ Backing material	PVC film	▪ Adhesion to steel	5.8 N/cm
▪ Total thickness	850 µm	▪ Elongation at break	25 %
▪ Type of adhesive	acrylic	▪ Temperature resistance	-5 to +50 °C

Properties

▪ Hand tearability	● ● ●	▪ Salt water resistant	● ● ●
▪ Suitable for die cutting	yes	▪ Fluorescent	yes
▪ Resistance to chemicals	● ● ●		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=60953>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.